Amendments to the Claims

Please cancel claims 14, 15, 28-32, 35, 37-40, 44-47, 54-58, 60-65, 67-123, and 125-130 without prejudice to inclusion of the subject matter of the canceled claims in one or more other patent applications.

Please amend the claims to read as follows:

- 1. (Original) A plastic comprising a polymer admixed with a mineralized ash filler.
- 2. (Original) The plastic of claim 1, wherein the polymer is a thermoplastic.
- 3. (Original) The plastic of claim 2, wherein the polymer is substantially a homopolymer selected from the group consisting of polyolefins, polyoxymethylenes, polystyrenes, polyamides, polyimides, polyesters, fluoropolymers, polyacrylates, polyarylates, polyaryletherketones, polynitriles, polybenzimidazoles, polycarbonates, polyethers, polyphenylene ethers, polyphenylene sulfides, polysulfones, polyaryl sulfones, polyvinyl chlorides, and polyurethanes.
- 4. (Original) The plastic of claim 2, wherein the polymer is a copolymer of at least two polymers selected from the group consisting of polyolefins, polyoxymethylenes, polystyrenes, polyamides, polyimides, polyesters, fluoropolymers, polyacrylates, polyarylates, polyaryletherketones, polynitriles, polybenzimidazoles, polycarbonates, polyethers, polyphenylene ethers, polyphenylene sulfides, polysulfones, polyaryl sulfones, polyvinyl chlorides, and polyurethanes.
- 5. (Original) The plastic of claim 2, wherein the polymer is a polymer of at least one monomer selected from the group consisting of ethylene, propylene, 1-pentene, 1-butene, 4-methyl-1-pentene, 1-hexene, 1-octene, 1-decane, styrene, acrylonitrile, maleic anhydride, butadiene, ethylidene norbornene, 1,4-hexadiene, 1,5-hexadiene, 1,7-octadiene, 1,9-decadiene, vinyl chloride, and dicyclopentadiene.

Application on 27 June 2003

6. (Original) The plastic of claim 2, wherein the polymer is a blend of at least two polymers selected from the group consisting of polyolefins, polyoxymethylenes, polystyrenes, polyamides, polyimides, polyesters, fluoropolymers, polyacrylates, polyarylates, polyaryletherketones, polynitriles, polybenzimidazoles, polycarbonates, polyethers, polyphenylene ethers, polyphenylene sulfides, polysulfones, polyaryl sulfones, polyvinyl chlorides, and polyurethanes.

(VW-8777)

- 7. (Original) The plastic of claim 6, wherein the polymers are miscible.
- 8. (Original) The plastic of claim 6, wherein the polymers are immiscibly blended.
- 9. (Original) The plastic of claim 1, wherein the polymer is a thermoset.
- 10. (Original) The plastic of claim 9, wherein the polymer is selected from the group consisting of diallyl phthalates, amine-formaldehyde polymers, cyanate esters, epoxies, phenolics, unsaturated polyesters, bismaleimides, polyurethanes, silicones, acrylamates, and vinyl esters.
- 11. (Original) The plastic of claim 1, comprising not more than about 60% by weight mineralized ash filler.
- 12. (Original) The plastic of claim 1, comprising not more than about 40% by weight mineralized ash filler.
- 13. (Original) The plastic of claim 1, comprising not more than about 25% by weight mineralized ash filler.
- 14-15. (Canceled)
- 16. (Original) The plastic of claim 1, wherein the composition comprises the mineralized ash filler in an amount sufficient to lower the viscosity of the composition at a temperature in the

U.S. Patent Application Ser. No. Not Yet Assigned **Preliminary Amendment Filed with**

Application on 27 June 2003

ATTORNEY DOCKET NO: D0932-00356

(VW-8777)

range 170 to 270 degrees Celsius, relative to the viscosity of the polymer alone at the same temperature and shear rate.

- 17. (Original) The plastic of claim 1, wherein the mineralized ash filler comprises a mineralized fly ash.
- 18. (Original) The plastic of claim 17, wherein the mineralized fly ash is obtained from a coalburning furnace.
- 19. (Original) The plastic of claim 17, wherein the leachable metal content of the mineralized fly ash is not greater than about 10 milligrams per milliliter, as assessed using ASTM Standard Test Method D3682-01.
- 20. (Original) The plastic of claim 17, wherein the leachable metal content of the mineralized fly ash is not greater than about 5 milligrams per milliliter, as assessed using ASTM Standard Test Method D3682-01.
- 21. (Original) The plastic of claim 17, wherein the leachable metal content of the mineralized fly ash is not greater than about 2 milligrams per milliliter, as assessed using ASTM Standard Test Method D3682-01.
- 22. (Original) The plastic of claim 17, wherein the leachable metal content of the mineralized fly ash is not greater than about 1 milligram per milliliter, as assessed using ASTM Standard Test Method D3682-01.
- 23. (Original) The plastic of claim 17, wherein i) the leachable lead content of the mineralized fly ash is not greater than about 0.2 milligram per milliliter; ii) the leachable chromium content of the mineralized fly ash is not greater than about 0.5 milligram per milliliter; and iii) the leachable cadmium content of the mineralized fly ash is not greater than about 0.1 milligram per milliliter, as assessed using ASTM Standard Test Method D3682-01.

- 24. (Original) The plastic of claim 17, wherein not more than about 1% by weight of the ash particles are retained on an American Standard Sieve Series (ASSS) No. 30 sieve.
- 25. (Original) The plastic of claim 17, wherein not more than about 1% by weight of the ash particles are retained on an ASSS No. 50 sieve.
- 26. (Original) The plastic of claim 17, wherein not more than about 5% by weight of the ash particles are retained on an ASSS No. 100 sieve.
- 27. (Original) The plastic of claim 17, wherein not more than about 25% by weight of the ash particles are retained on an ASSS No. 200 sieve.
- 28-32. (Canceled)
- 33. (Original) The plastic of claim 1, further comprising a second filler.
- 34. (Original) The plastic of claim 33, wherein the second filler is a nanofiller.
- 35. (Canceled)
- 36. (Original) The plastic of claim 34, wherein the nanofiller is a nanoclay.
- 37-40. (Canceled)
- 41. (Amended) The plastic of claim-40 36, wherein the nanoclay is montmorillonite that has been surface-treated to decrease association of nanoclay particles with one another.
- 42. (Original) The plastic of claim 36, comprising not more than about 7% by dry weight of the nanoclay.

43. (Original) The plastic of claim 36, wherein the number average maximum dimension of the nanoclay particles is not greater than about 500 nanometers.

44-47. (Canceled)

48. (Original) A manufactured article comprising the plastic of claim 1.

49. (Original) The article of claim 48, formed into a building material.

50. (Original) The article of claim 49, wherein the building material is selected from the group consisting of roofing, siding, insulation, piping, railing, fencing, decking, flooring, framing, and trimming materials.

51. (Original) The article of claim 49, wherein the building material is a plank.

52. (Original) The article of claim 49, wherein the building material is an ornamental building material.

53. (Original) The article of claim 49, wherein the building material is a structural building material.

54-58. (Canceled)

59. A method of making a plastic, the method comprising incorporating a mineralized ash filler into a polymer resin and thereafter solidifying the resin to form the plastic.

60-65. (Canceled)

ATTORNEY DOCKET NO: D0932-00356 (VW-8777)

U.S. Patent Application Ser. No. Not Yet Assigned Preliminary Amendment Filed with Application on 27 June 2003

66. (Amended) The method of claim-65 59, wherein the polymer is formed into a shape selected from the group consisting of a plank, a sheet, a tube, and a pellet prior to solidifying the resin.

67-123. (Canceled)

124. (Original) A method of increasing the tensile modulus of a plastic, the method comprising incorporating up to about 60% by weight of a mineralized ash filler into the plastic.

125-130. (Canceled)